

# 洗墙灯 WWL1202

现代简约设计，配光齐全，

散热性能好，寿命长，产品可以兼容DMX512或RDM控制系统，

结构防水，安装方便，维护简单，

适用于户外洗墙，桥梁亮化，景观亮化以及各种建筑体的专业照明工程。



R/G/B/W



易于安装



可选择  
亮度调光



可支持  
极端环境



IP65




DC-IN

## 规格参数

|      |                            |
|------|----------------------------|
| 型 号  | ▶ WWL1202                  |
| 工作电压 | ▶ 12V DC, 24V DC           |
| 功 率  | ▶ 12W/24W                  |
| 光源类型 | ▶ LED 2835/LED 3030        |
| 色 温  | ▶ 2700K, 3000K, 4000K      |
| 频 率  | ▶ 90min, 80min             |
| 光源效率 | ▶ 110 lm/W@3000K           |
| 发光角度 | ▶ 22°/20°*40°/45°          |
| 材 质  | ▶ 优质铝 + 钢化玻璃               |
| 工作温度 | ▶ -20°C ~ +55°C            |
| 储存温度 | ▶ -25°C ~ +60°C            |
| 光源寿命 | ▶ 50,000 hours/L70 at 25°C |
| 通电连接 | ▶ 快速接头 (可选)                |
| 产品尺寸 | ▶ 1002*29*38(H)mm          |
| 防护等级 | ▶ IP65                     |
| 控制方式 | ▶ ON/OFF                   |
| 证 书  | ▶ CE & ROHS                |

## 产品尺寸

Unit: mm



## 配光曲线

