

# 洗墙灯 WWL2408

现代简约设计，配光齐全，

散热性能好，寿命长，产品可以兼容DMX512或RDM控制系统，

结构防水，安装方便，维护简单，

适用于户外洗墙，桥梁亮化，景观亮化以及各种建筑体的专业照明工程。



R/G/B/W



易于安装



可选择  
亮度调光



可支持  
极端环境



IP65




DC-IN

## 规格参数

型 号	▶ WWL2408
工作电压	▶ 12V DC, 24V DC
功 率	▶ 12W/24W
光源类型	▶ LED 2835/LED 3030
色 温	▶ 2700K, 3000K, 4000K
频 率	▶ 90min, 80min
光源效率	▶ 110 lm/W@3000K
发光角度	▶ 22°/20°*40°/45°
材 质	▶ 优质铝 + 钢化玻璃
工作温度	▶ -20°C ~ +55°C
储存温度	▶ -25°C ~ +60°C
光源寿命	▶ 50,000 hours/L70 at 25°C
通电连接	▶ 快速接头 (可选)
产品尺寸	▶ 1002*29*38(H)mm
防护等级	▶ IP65
控制方式	▶ ON/OFF
证 书	▶ CE & ROHS

产品尺寸

Unit: mm



配光曲线

